(210) 599-6485 (888) 853-8944

Electrol Systems, Inc.

MOTOR STARTERS

FAX (210) 599-6487 FAX (888) 853-8945

CUSTOMER:		
PROJECT:	BID DATE:	
STANDARD PACKAGE INCLUDES:	INSTALL AND WIRE OPTIONS: (SUCH AS HAND-OFF-AUTO SELECTOR SWITCH) PERFORM ALL ELECTRICAL TESTS ON CIRCUITRY. INSTALL ADJUSTABLE OVERLOAD RELAYS TO THE RANGE REQUIRED PER FLA (FULL LOAD AMPS). FURNSIH WIRING DIAGRAM FOR EACH STARTER (SUCH AS: AHU-1 or EF1). PROVIDE PHONE SUPPORT FOR IN FIELD PROBLEMS OR QUESTIONS CONCERING THE INSTALLATION AND APPLICATION OF OUR EQUIPMENT.	
QUANTITY:		STARTER TO BE USED FOR:
STARTER TYPE:	☐ OPEN ☐ ENCLOSED ENCLOSURE TYPE: ☐ NEMA 1 (INDOOR) ☐ NEMA 3R (OUTDOOR) ☐ NEMA 12 (INDOOR-DUST RESISTANT) ☐ NEMA 4 (INDOOR/OUTDOOR - WATER / ICE RESISTANT) ☐ NEMA 4X (INDOOR/OUTDOOR - WATER RESISTANT & RESISTS CORROSION (☐ FIBERGLASS or ☐ STAINLESS STEEL)	
VOLTAGE:	☐ 120V/ SINGLE PHASE ☐ 240 V/ SINGLE PHASE ☐ 208 V/ THREE PHASE ☐ 480 V/ THREE PHASE	□ OTHER:
FREQUENCY:	□ 50 Hz	□ 60 Hz
HORSEPOWER:		R.P.M. (IF AVAILABLE):
RUNNING AMPS:		MOTOR VOLTAGE:
COIL VOLTAGE:	☐ 24 V ☐ DC ☐ AC ☐ 120VAC ☐ 208 VAC ☐ 240 VDC	☐ 480 VAC ☐ OTHER:
OPTIONS:	□ HAND-OFF-AUTO SWITCH □ PILOT LAMP ON (□ R □ G) □ AUXILIARY CONTACTS □ OTHER:	□ START-STOP SWITCH □ PILOT LAMP OFF (□ G □ R) □ NORMALLY CLOSED □ NORMALLY OPEN
QUOTATION #:	\$	DATE: